

VIRAJ XTD-20

divinity lights



Quick Info

CRI ≥ 90

3000K/ 4000K/ 5700K

TUNABLE WHITE 2700-6500K

ON-OFF/ ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI+

SDCM <3

Lens

L70 @50,000h

Aluminium

Types



Pendant/ Surface

Single Line Diagram

Pendant Mounted

Profile Code

SY-136




VIRAJ XTD-20

Viraj XTD-20 linear fixture has :

- Extruded Aluminium Luminaire Housing
- Premium Finish Powder coating
- Snap fit system with No visible screw
- Deep recessed lens System
- Beam angles ranging from 24°/50°/50°x50°
- Energy efficient LED with high colour rendering
- LED PCB mounted on insert design with heat sink
- Pendant using suspension cable with M6 bolt and fastener
- Bottom opening for easy maintenance

Light Distribution

Direct



CRI ≥ 90



TUNABLE
WHITE

VIRAJ XTD-20



VIRAJ XTD-20 (DIRECT)

System Power	Dimensions
6W	L = 300mm
12W	L = 600mm
18W	L = 900mm
25W	L = 1200mm
50W	L = 2400mm

Order Options

Distribution

- Direct
- Indirect
- Up-50% / Down-50%
- Up-30% / Down-70%
- Up-70% / Down-30%
- Up-20% / Down-80%
- Up-80% / Down-20%

CCT (Color Temperature)

- 3000K
- 4000K
- 5700K
- Tunable 2700K-6500K



CRI

>90

Beam Angle

- 24°
- 50°

Control

- ON-OFF
- ON-OFF (FLICKER FREE)
- DALI-2 DT6
- DALI-2 DT8
- DALI +



Mounting Type

- Pendent
- Surface
- Recessed

Material Color

RAL As Per Request

Photometric

