



Amandeep COB Spot light Downlighter is Fixed led Downlight made up of die cast aluminium housing and with premium powder coated finish.

Powered by high quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90 . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency optics with beam 110° with Diffuser along with Anti-glare reflector gives uniform and zero multiple shadow illumination.

Amandeep recessed Downlighter available in 7W, 15W and 25W is crafted for direct light distribution making it ideal for residential & professional applications.

Product Name	Wattage	Beam Angle	Dimension Dia x Ht(mm)
Amandeep 7	7W	110° Diffuser	OuterØ-83, CutoutØ-67, Ht-53
Amandeep 15	15W	110° Diffuser	OuterØ-101, CutoutØ-90, Ht-70
Amandeep 25	25W	110° Diffuser	OuterØ-137, CutoutØ-126, Ht-97

AMANDEEPDOWNLIGHTER









Quick Info

Mounting Type

Recessed

Material Colour

Customize RAL avilable

Protection mode

IP40

McAdam- 3

Power Factor (PF) - 0.95

THD - <10%

UGR - <21

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span-L70 @ 50000h **MacAdam-** ≤ 3 SDC*M*

Efficacy-102.7lm/w

Control

DALI DIMMABLE/ NON DIMMABLE/ DALI-2 DT8

Beam Angle

110°

Optics

Diffuser

Electrical

Wattage - 7W,15W, 25W **Input-** 220-240 VAC

Single Line Diagram

Amandeep 7

Amandeep 15

Amandeep 25







