3D BEND 20
LED STRIP

Quick Info

CRI ≥ 90
2700K, 3000K, 4000K, RGB, RGBW
Beam Angle 120°
Silicon finish
PCB Width 10 MM (TOP & SIDE)
IP Rating IP67
Non-Dimmable/ Dali-Dimmable
SDCM<3
L70 @50,000h

**Type**

Surface

Single Line Diagram

3D BEND 20

3D Bend 20 fixture has :

•   Circular tube design with 360° light emitting performance, available to build many

     patterns and arts for decoration.

•   Bend to form easily and fast with built-in metal frame design.

•   Uniform, dot-free, smooth and comfortable luminary up to 5M[16.4ft.] run length.

•   Customized length with overall appearance in the same size by die-casting process.

•   IP67 for indoor and outdoor usage.

•   Silicon extrusion technology is an advanced process,

3D BEND 20

| INPUT VOLTAGE 24V DC | IP67 | | CRI ≥ 90 |

Product order code	System Power	Dimensions
2814	12W/MTR	20 MM X 20 MM

Order Options

CCT (Color Temperature)

2700K

3000K

4000K

RGB

RGBW

CRI

>90

Beam Angle

180°

Control

Non-Dimmable

Dali- Dimm

RGB DMX512

NON-Dimmable

DA LI

Mounting Type

Surface