


VIRAJ 45

Direct | Recessed



VIRAJ 45



Quick Info

Mounting Type

Recessed

Material Colour

Customize RAL available

Protection mode

IP40

McAdam- 3

Power Factor (PF) - 0.95

THD - <10%

UGR - <21

LED

CCT- 3000K/4000K/5700K/TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span-L70 @ 50000h

MacAdam- ≤ 3 SDCM

Efficacy-118lm/w

Control

DALI DIMMABLE/ NON DIMMABLE/ DALI-2 DT8

Beam Angle

Diffused

Optics

Opal Diffuser

Prismatic Diffuser

Electrical

Std Wattage - 25W/4ft

Opt Wattages Available - 15W/ 4ft, 20W/ 4ft

Input- 220-240 VAC

Physical

Length- 1200 mm

Height- 70 mm

Width- 56 mm

VIRAJ 45 Linear Luminaire in a sleek design with a slim Extruded aluminum housing and with premium powder coating finish.

Powered by high-quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90 . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long-term reliability. HPO diffuser (High-Performance Opal/ PMMA diffuser) provides uniform illumination.

With a standard size of 1200 mm length, 70 mm height, and 46 mm width, this fixture is crafted for direct light distribution making it ideal for professional applications.

Customisations in RAL finish, Wattages and Length available as per request to enhance installation and functionality.

Single Line Diagram

Recessed

