

divinity lights

ARES-U



divinity lights

Quick Info

CRI ≥ 90
3000K/ 4000K/ 5700K
Tunable White 2700-6500K
ON-OFF/ ON-OFF (FLICKER FREE)
DALI-2 DT6 / DALI-2 DT8/ DALI+
SDCM <3
Lens
L70 @50,000h
Aluminium


Types

Pendant/Surface


Single Line Diagram

Pendant/Surface Mounted

Profile Code
SDL-3005




Profile Code
SDL-3006



Ares-U

Ares-U Fixture has

- Extruded Aluminium Luminaire Housing
- Premium Finish Powder coating
- High efficiency Lens
- Energy efficient LED with high colour rendering
- LED PCB mounted on insert design with heat sink
- Snap-fit system and no visible screw
- Unique curved design and patterns possible
- Pendant using suspension cable with M6 bolt and fastener
- Bottom opening for easy maintenance



CRI ≥ 90



TUNABLE WHITE

ARES-U



ARES-U (DIRECT)

System Power	Dimensions
5W	L = 300mm
10W	L = 600mm
15W	L = 900mm
20W	L = 1200mm
40W	L = 2400mm

Order Options

Distribution

Direct

CCT (Color Temperature)

3000K
 4000K
 5700K
 Tunable 2700K-6500K



CRI

>90

Beam Angle

24°
 38°
 55°

Control

ON-OFF
 ON-OFF (FLICKER FREE)
 DALI-2 DT6
 DALI-2 DT8
 DALI +



Mounting Type

Pendent

Material Color

RAL As Per Request