



ARYA Downlighter is Fixed led Downlight made up of die cast aluminium housing and with premium powder coated finish.

Powered by high quality LED's with a binning tolerance of \leq 3 SDCM and CRI \geq 90. The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency optics with beam angle options of 15°, 30° and 45° gives uniform and zero multiple shadow illumination.

ARYA 4

Arya Downlighter available in 5 variants Arya 4 in 7W, 4 modules, square shape, this fixture is crafted for direct light distribution making it ideal for residential & professional applications

Options in reflector finish available as per request to enhance installation and functionality.

Single Line Diagram

Recessed

ARYA 4



ARYA 4









Quick Info

Mounting Type

Recessed

Material Colour

Customize RAL avilable

Protection mode

IP44

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤3 SDCM

Beam Angle

15°/ 30°/ 45°

Optics

Lens Reflector

Efficacy

3000K- 63.0 4000K- 72.7 5700K- 81.0 Tunable White 2700K-6500K- 72.7

Electrical

Wattage - 7W Input Voltage - 220-240 VAC

Physical

Outer Dia- LXW = 50x50mm
Cutout Dia- LXW = 43x43mm
Height- 40mm

