

AURA RING

Direct | Pendant



AURA RING is Inner lit Ring luminaire in aluminium housing and with premium powder coating finish.

Powered by high quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90 . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency Acrylic diffuser provides uniform illumination and unique inner glow.



FOR 1200mm Disc

Available in 1200mm diameter and with height of 85mm, this fixture is crafted for side lit light distribution making it ideal for professional and decorative applications.

Customisations in RAL finish, Wattages and Dimensions available as per request to enhance installation and functionality.

Single Line Diagram

Pendant



AURA RING



Quick Info

Mounting Type

Pendant

Material Colour

Customize RAL available

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

110°

Optics

Acrylic Diffuser

Efficacy

3000K- 97.5

4000K- 124.5

5700K- 137.1

Tunable White 2700K-6500K- 124.5

Electrical

Wattage -60W

Input Voltage- 220-240 VAC

Physical Dimensions

Dia- \varnothing 1200mm

Height- 85mm