

CURVE SOFT 28

divinity lights





CURVE SOFT 28

Curve soft 28 has :

- LED curved linear
- Extruded Aluminium Luminaire Housing
- High efficiency Micro Prismatic/ PMMA Diffuser
- Uniform illumination
- Infinite architectural designs and circular patterns possible
- Energy efficient LED with high colour rendering
- LED PCB mounted
- For pendant or recessed mounted applications
- Pendant using suspension cable with M6 bolt and fastener
- Bottom opening for easy maintenance

Quick Info

CRI ≥ 90

3000K/ 4000K/ 5700K

Tunable white (2700K-6500K)

ON-OFF/ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI+

SDCM<3

Micro Prismatic Diffuser/PMMA

L70 @50,000h

Aluminium



Types

Pendant/Recessed

Single Line Diagram

Profile Code

SDL-1036



CRI ≥ 90



TUNABLE
WHITE

CURVE SOFT 28



CURVE SOFT 28

System Power	Dimensions
6W	L= 300mm W=28.5mm, H= 30mm
12W	L= 600mm W=28.5mm, H= 30mm
18W	L= 900mm W=28.5mm, H= 30mm
25W	L= 1200mm W=28.5mm, H= 30mm
50W	L= 2400mm W=60mm, H= 30mm

Order Options

Distribution

Direct

CCT (Color Temperature)

3000K
4000K
5700K
Tunable 2700K-6500K



CRI

>90

Beam Angle

Diffused

Control

- ON-OFF
- ON-OFF (FLICKER FREE)
- DALI-2 DT6
- DALI-2 DT8
- DALI +



Mounting Type

- Pendent
- Recessed

Material Color

RAL As Per Request

Photometric Details

LUMINOUS INTENSITY DISTRIBUTION

