

**CURVE SOFT 50**

**divinity lights**





## CURVE SOFT 50

Curve soft 50 has :

- LED curved linear
- Extruded Aluminium Luminaire Housing
- Premium Finish Powder coating
- High efficiency Micro Prismatic/ PMMA Diffuser
- Uniform illumination
- Dot-free lighting and smart arc linear
- Infinite architectural designs and circular patterns possible
- Energy efficient LED with high colour rendering
- LED PCB mounted
- For pendant or recessed mounted applications
- Pendant using suspension cable with M6 bolt and fastener
- Bottom opening for easy maintenance

### Quick Info

CRI  $\geq 90$

3000K/ 4000K/ 5700K

Tunable white (2700K-6500K)

ON-OFF/ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI+

SDCM $<3$

Micro Prismatic Diffuser/PMMA

L70 @50,000h

Aluminium



### Types

Pendant/Recessed

### Single Line Diagram

#### Profile Code

SDL-1048



CRI  $\geq 90$



TUNABLE  
WHITE

**CURVE SOFT 50**



**CURVE SOFT 50**

System Power	Dimensions
7W	L= 300mm W= 50mm, H= 31mm
14W	L= 600mm W= 50mm, H= 31mm
21W	L= 900mm W= 50mm, H= 31mm
28W	L= 1200mm W= 50mm, H= 31mm
56W	L= 2400mm W= 50mm, H= 31mm

**Order Options**

**Distribution**

Direct

**CCT (Color Temperature)**

3000K  
4000K  
5700K  
Tunable 2700K-6500K



**CRI**

>90

**Beam Angle**

Diffused

**Control**

ON-OFF  
ON-OFF (FLICKER FREE)  
DALI-2 DT6  
DALI-2 DT8  
DALI +



**Mounting Type**

Pendent  
Recessed

**Material Color**

RAL As Per Request

**Photometric Details**

