

**DAISY CRESENT
PRISMATIC**

divinity lights



Quick Info

CRI ≥ 80/ 90/ 95

3000K/ 4000K/ 5700K/ 6500K

Tunable White 2700K-6500K

Up to 100lm/W

ON-OFF/ON-OFF (FLICKER FREE)

DALI-2 / DALI-2 DT8 / D4i / DALI +

POE (Power Over Ethernet)

SDCM<3

Micro Prismatic Diffuser

L70 @ 50,000h



Aluminium

Types

Pendant/ Surface

Single Line Diagram

Pendant/ Surface



Micro Prismatic Diffuser



DAISY CRESENT PRISMATIC

Daisy Cresent Prismatic sleek linear fixture has:


- Luminaire housing of extruded aluminium
- Surface powder coated
- Snap-fit system and no visible screw
- High-performance Prismatic double diffuser
- Better refractive index to reduce glare
- LED PCB mounted on insert design with heat sink
- Bottom opening for easy maintenance
- Pendant with cable suspension
- M6 bolt for M6 fastener
- Energy-efficient LED with color rendering

Colours



Light Distribution

Direct



CRI ≥ 80/ 90/ 95



TUNABLE
WHITE

DAISY CRESENT PRISMATIC



DAISY CRESENT PRISMATIC (DIRECT)

Product Order Code	System Power	Dimensions
1014-1	6W	L = 300mm, W = 80mm, H = 99mm
1014-2	12W	L = 600mm, W = 80mm, H = 99mm
1014-3	18W	L = 900mm, W = 80mm, H = 99mm
1014-4	25W	L = 1200mm, W = 80mm, H = 99mm
1014-5	50W	L = 2400mm, W = 80mm, H = 99mm

Order Options

Distribution

Direct

Lumen Type

Low	1
High	2

CCT (Colour Temperature)

3000K	1
4000K	2
5700K	3
6500K	4
Tunable White 2700K-6500K	5

CRI

>80	1
>90	2
>95	3

Beam Angle

110°

Control

ON-OFF	1
ON-OFF (FLICKER FREE)	2
DALI-2	3
DALI-2 DT8	4
DALI +	5
D4i	6
POE (Power Over Ethernet)	7







Mounting Type

Pendant	1
Surface	2

Material Colour

Black	1
White	2
Grey	3

Accessories


Product Order Code	Accessories Name	Accessories Image
1014-01 <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	LED PCB	
1014-02	Suspension Wire	
1014-03	PMMA Diffuser	
1014-04	Micro Prismatic Diffuser	
1014-05	Profile Connector	
1014-06 <input type="checkbox"/>	Profile Endcap	

Order Options

Lumen Type

- Low 1
- High 2

CCT (Colour Temperature)

- 3000K 1
- 4000K 2
- 5700K 3
- 6500K 4
- Tunable White 2700K-6500K  5

CRI

- >80 1
- >90 2
- >95 3

Material Colour

- Black 1
- White 2
- Grey 3