

## FIRE FOX RING

Direct | Pendant



**FIRE FOX RING** is Concentric circle ring luminaire in aluminium + acrylic housing and with premium powder coating finish.

Powered by high quality LED's with a binning tolerance of  $\leq 3$  SDCM and CRI  $\geq 90$ . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency Acrylic provides glare control and uniform illumination.



### For 355mm Ring

Available in 355mm diameter and with height 90mm, this fixture is crafted for direct light distribution making it ideal for home decoration & professional applications.

Customisations in Wattages and Dimensions available as per request to enhance installation and functionality.

### Single Line Diagram

Pendant



## FIRE FOX RING

## FIRE FOX RING



## Quick Info

### Mounting Type

Pendant

### Material Colour

Customize RAL available

### Protection mode

IP40

### Driver Details

ON/OFF, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

### LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI-  $\geq 90$

Life Span - L70@50000h

MacAdam -  $\leq 3$  SDCM

### Beam Angle

110°

### Optics

Acrylic Diffuser

### Efficacy

3000K- 79.1

4000K- 94.6

5700K- 112.4

Tunable White 2700K-6500K- 94.6

### Electrical

Wattage -25W

Input Voltage- 220-240 VAC

### Physical Dimensions

Length- Ø355mm

Height- 90mm