

# GE MACTY

Direct | Pendant

## GE MACTY

GE MACTY



## Quick Info

### Mounting Type

Pendant

### Material Colour

Customize RAL available

### Protection mode

IP40

### Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

### LED

CCT- Tunable White 2700K-6500K

CRI-  $\geq 90$

Life Span - L70@50000h

MacAdam -  $\leq 3$  SDCM

### Beam Angle

12°/24°/36°/55°

### Optics

Lens

### Efficacy

Tunable White 2700K-6500K- 124.1

### Electrical

Wattage - 16W

Input Voltage- 220-240 VAC

### Physical

Dia- 100mm

Height- 150mm

**GE MACTY** COB Downlighter is Cylindrical led Downlight made up of die cast aluminium housing, heat sink and with premium powder coated finish.

Powered by high quality COB with a binning tolerance of  $\leq 3$  SDCM and  $\text{CRI} \geq 90$ . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency optics with beam angle options of 15°, 24°, 36° and 55° gives uniform illumination


GE Macty Cylindrical Downlighter is crafted for direct light distribution making it ideal for residential, retail, hospitality & professional applications.

Customisations in RAL finish available as per request to enhance installation and functionality.

### Single Line Diagram

Surface

GE MACTY



**divinity lights**

Address: Plot No-A-89, RIICO Industrial Area, Karoli, Bhiwadi, Rajasthan 301019.

[www.divinitylights.com](http://www.divinitylights.com)