








HERCULES





HERCULES DOWNLIGHT

Hercules Downlight features has:

- Die cast- aluminium Luminaire housing
- Premium powder coated finish
- COB (Chip on Board) technology
- Lens with honeycomb louver
- Available in Fixed version
- LED with effective colour rendering
- Provides comfortable illumination with reduced eye strain, ideal for premium interiors.
- Delivers focused and controlled light distribution for accent
- Ensures excellent lumen output with low energy consumption.

Quick Info


CRI ≥ 90
 3000K/ 4000K/ 5700K
 ON-OFF/ON-OFF (FLICKER FREE)
 DALI-2 DT6, DALI-2 DT8, DALI+
 SDCM<3
 Lens with Honeycomb Louver
 L70 @50,000h

Types


Recessed

Single Line Diagram


Hercules 40



Hercules 52




Hercules 68



Light Distribution

Direct



CRI ≥ 90



TUNABLE
WHITE

HERCULES DOWNLIGHT



HERCULES 40

System Power	Dimension
5W	Outer Dia- 47mm, Cutout Dia- 40mm, Height- 56mm

HERCULES 52

System Power	Dimension
10W	Outer Dia- 59mm, Cutout Dia- 52mm, Height- 64mm

HERCULES 68

System Power	Dimension
15W	Outer Dia- 89mm, Cutout Dia- 68mm, Height- 90.5mm

Order Options

CCT (Colour Temperature)

3000K

4000K

5700K

Tunable White 2700K-6500K



CRI

>90

Beam Angle

10°

15°

24°

36°

50°

Control

ON-OFF



ON-OFF (FLICKER FREE)



DALI-2 DT6



DALI-2 DT8



DALI+



Mounting

Recessed

Reflector Colour

Black

White

Gold

Rose Gold

Material Colour

RAL As Per Request