

HERCULES DARK



Quick Info


CRI ≥ 90
3000K/ 4000K/ 5700K
ON-OFF/ON-OFF (FLICKER FREE)
DALI-2 DT6, DALI-2 DT8, DALI+
SDCM<3
Lens
L70 @50,000h

Types


Recessed

Single Line Diagram


Hercules 40




Hercules 52



Hercules 68



Light Distribution



CRI ≥ 90



TUNABLE
WHITE

HERCULES DARK DOWNLIGHT

Hercules Dark Downlight features has:

- Die cast- aluminium Luminaire housing
- Premium powder coated finish
- COB (Chip on Board) technology with Lens
- Available in Fixed version
- LED with effective colour rendering
- Provides comfortable illumination with reduced eye strain, ideal for premium interiors.
- Delivers focused and controlled light distribution for accent
- Ensures excellent lumen output with low energy consumption.

HERCULES DARK



HERCULES DARK 40

System Power	Dimension
5W	Outer Dia- 47mm, Cutout Dia- 40mm, Height- 56mm

HERCULES DARK 52

System Power	Dimension
10W	Outer Dia- 59mm, Cutout Dia- 52mm, Height- 64mm

HERCULES DARK 68

System Power	Dimension
15W	Outer Dia- 75mm, Cutout Dia- 68mm, Height- 90.5mm

Order Options

CCT (Colour Temperature)

3000K

4000K

5700K

Tunable White 2700K-6500K



CRI

>90

Beam Angle

10°

15°

24°

36°

50°

Control

ON-OFF



ON-OFF (FLICKER FREE)



DALI-2 DT6



DALI-2 DT8



DALI+



Mounting

Recessed

Reflector Colour

Black

White

Gold

Rose Gold

Material Colour

RAL As Per Request