HORIZON-S
WALL LIGHTS

Direct | Surface



HORIZON-S WALL LIGHT luminaire features a sleek, modern design crafted from aluminium die-cast housing with a premium powder-coated finish.


Powered by high-quality LEDs with a binning tolerance of ≤ 3 SDCM and CRI ≥ 80, this fixture ensures excellent color rendering and long-lasting performance. It maintains at least 70% of its luminous flux after 50,000 operating hours, guaranteeing durability and reliability over time. The high-efficiency **Tempered Glass** delivers a soft, uniform 12°/ 24°/ 36° and 60° beam ideal for outdoor wall-mounted applications, providing cozy, glare-free downward illumination. With IP65-rated waterproof construction and availability in both round and square shapes, HORIZON-S WALL LIGHT is perfect for entrances, terraces, and architectural facades.

With a standard size of 100mm Dia, and 150mm height, this fixture is crafted for direct light distribution, making it ideal for professional application.

Customisations in RAL finish, wattages, and Length available as per request to enhance installation and functionality.

Single Line Diagram

Surface Mounted



HORIZON-S WALL LIGHTS



Quick Info

Mounting Type
Surface

Material Colour
Customize RAL available

Protection mode
IP65

Driver Details
Non-Dimmable/ Dali-Dimmable

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED
CCT- 2700K/ 3000K/ 4000K

CRI- ≥ 80

Life Span - L70@50000h

MacAdam - ≤3 SDCM

Beam Angle
12°/ 24°/ 36°/ 60°

Optics
Tempered Glass

Efficacy
80lm/W

Electrical
Wattage - 10W

Input Voltage- 220-240V AC

Physical Dimensions
LXW- 100X100mm

Height- 150mm

divinity lights

Address: Plot No-A-89, RIICO Industrial Area, Karoli, Bhiwadi, Rajasthan 301019.

www.divinitylights.com