IKON-S
STEP LIGHTS

Direct | Recessed



IKON-S STEP LIGHT luminaire features a sleek, modern design crafted from aluminium die-cast housing with a premium powder-coated finish.


Powered by high-quality LEDs with a binning tolerance of ≤ 3 SDCM and CRI ≥ 80, this fixture ensures excellent color rendering and long-lasting performance. It maintains at least 70% of its luminous flux after 50,000 operating hours, guaranteeing durability and reliability over time. High-efficiency **Clear Glass** provides uniform illumination and reduces glare.

With a standard size of 70mm Length, 70mm Width and 45mm Height, this fixture is crafted for direct light distribution, making it ideal for professional application.

Customisations in RAL finish, wattages, and Length available as per request to enhance installation and functionality.

Single Line Diagram

Recessed Mounted



IKON-S STEP LIGHTS



Quick Info

Mounting Type
Recessed

Material Colour
Customize RAL available

Protection mode
IP65

Driver Details
Non-Dimmable/ Dali-Dimmable

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED
CCT- 2700K/ 3000K/ 4000K

CRI- ≥ 80

Life Span - L70@50000h

MacAdam - ≤3 SDCM

Beam Angle
60°

Optics
Clear Glass

Efficacy
80lm/W

Electrical
Wattage - 3W

Input Voltage- 220-240V AC

Physical Dimensions
Length- 70mm

Width- 70mm

Height- 45mm

divinity lights

Address: Plot No-A-89, RIICO Industrial Area, Karoli, Bhiwadi, Rajasthan 301019.

www.divinitylights.com