

LENO D- DIRECT


Direct | Task Lights



LENO D Luminaire housing of aluminum with premium powder coating finish. Powered by high-quality LED's with a binning tolerance of ≤ 3 SDCM and $CRI \geq 90$. The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long-term reliability. Optics of high efficiency lens & reflector for uniform light distribution. With a Customize size, this fixture is crafted for direct light distribution making it ideal for professional applications. Numerous combination of lamp Head design for vriety of desks. Customisations in RAL finish, Wattages available as per request to enhance installation and functionality.

Single Line Diagram

Surface Mounted



LENO D



Quick Info

Mounting Type

Surface

Material Colour

Powder Coated (Grey)

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

110°

Optics

Lens

Reflector

Efficacy

3000-

4000-

5700-

Tunable White 2700K-6500K-

Electrical

Wattage - 35W

Input Voltage- 220-240 VAC

Light Distribution

Direct - Down 100%

Physical

Customize Dimension