
LEXIS-RE
STEP LIGHT


divinity lights






divinity lights









LEXIS-RE

Lexis-RE Step light has :

- Luminaire housing of Die-Cast Aluminium
- IP65, High Ingress Protection against dust & moisture
- Extremely sustainable and requires little maintenance
- Lens optics for even light distribution
- Energy-efficient LED with high colour rendering
- Wall Light with integrated LED for orientation of pavements, stairs or terraces
- Excellent downward illumination with minimal power consumption
- Sleek & sophisticated round shape surface mounted LED light designed to elevate your outdoor lighting experience

Quick Info

CRI ≥ 80

2700K, 3000K, 4000K

70 lm/W

Non-Dimmable/ Dali-Dimmable

SDCM<3

Lens With Tempered Glass


L70 @50,000h

Aluminium Die-Cast


Types

Recessed

Single Line Diagram








CRI ≥ 80

divinity lights

LEXIS-RE



System Power	Dimensions
7W	LXW- 250X88mm, H- 72mm

Order Options

CCT (Colour Temperature)

2700K
3000K
4000K

CRI

>80

Beam Angle

Forward-Throw Distribution

Control

Non Dimmable

Dali Dimmable

Mounting Type

Recessed

Material Colour

RAL as per request