


ORBIT 40 TRIMLESS

Direct | Recessed

ORBIT 40



ORBIT 40 TRIMLESS is Premium range Recessed COB Spot light Downlighter available in Fixed and Adjustable version made up of die cast aluminium housing, heat sink and with premium powder coated finish.

Powered by high quality COB with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90 . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency optics lens

Louver (Lens with Honeycomb & Diffuser option available) with 4 beam angle options of 15°, 26°, 36°, 60° and precision engineered, electro and nano plated reflector with 6 types reflector cover options gives uniform and zero multiple shadow illumination



Orbit 40 Downlighter available in wattage from ranging from 5W is crafted for direct light distribution making it ideal for residential & professional applications.

Options in reflector cover available as per request to enhance installation and functionality.

Single Line Diagram

Recessed

ORBIT 40 TRIMLESS



ORBIT 40 TRIMLESS



Quick Info

Mounting Type

Recessed

Material Colour

Customize RAL available

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

15°, 24°, 35°, 60°

Optics

Lens

Efficacy

80lm/w

Electrical

Wattage - 5W

Input Voltage- 220-240 VAC

Physical

Dia- 40mm

Overall Width-110mm

Height-51mm