P1 WALL GRAZER

Direct | Surface



P1 WALL GRAZER is Surface mounted linear grazer Luminaire with Extruded aluminium housing and with premium powder coating finish.


Powered by high quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90. The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency optics with narrow beam angle options of 10° and 30°grazes wall vertically, reduces hot spots and gives uniform illumination.

With a standard size of 1000 mm length, 23mm width and 26mm height , this fixture is crafted for wall glazing making it ideal for professional applications.

Customisations in RAL finish, Wattages and Length available as per request to enhance installation and functionality.

Single Line Diagram

Surface



P1 WALL GRAZER



Quick Info

Mounting Type
Surface

Material Colour
Customize RAL avilable

Protection mode
IP40

Driver Details
ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +
Power Factor (PF) -0.95
THD- <10%
UGR - <19

LED
CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K
CRI- ≥ 90
Life Span - L70@50000h
MacAdam - ≤3 SDCM

Beam Angle
10°/ 30°

Optics
Lens

Efficacy
80lm/W

Electrical
Wattage - 4W/Mtr
Opt Wattages Available -8W/ 12W/ 15W
Input Voltage- 220-240V AC

Physical
Lenght- 300mm
Height- 26 mm
Width- 23 mm

divinity lights

Address: Plot No-A-89, RIICO Industrial Area, Karoli, Bhiwadi, Rajasthan 301019.

www.divinitylights.com