

P2 VERTICAL WALL GRAZER

Direct | Surface



P2 VERTICAL WALL GRAZER is Surface mounted linear grazer Luminaire with Extruded aluminium housing and with premium powder coating finish.


Powered by high quality LED's with a binning tolerance of ≤ 3 SDCM and $\text{CRI} \geq 90$. The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency optics with narrow beam angle options of 10° and 30° grazes wall vertically, reduces hot spots and gives uniform illumination.

With a standard size of 1000 mm length, 24.5mm width and 43mm height, this fixture is crafted for wall glazing making it ideal for professional applications.

Customisations in RAL finish, Wattages and Length available as per request to enhance installation and functionality.

Single Line Diagram

Surface



P2 VERTICAL WALL GRAZER



Quick Info

Mounting Type

Surface

Material Colour

Customize RAL available

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

10° / 30°

Optics

Lens

Efficacy

80lm/W

Electrical

Wattage - 12W/Mtr

Opt Wattages Available -4W/Mtr, 8W/Mtr

Input Voltage- 220-240 VAC

Physical

Length- 1000mm

Height- 43 mm

Width- 24.5 mm