


PG SLIM CURVE



Quick Info

CRI ≥ 90

3000K/ 4000K/ 5700K

Tunable white (2700K-6500K)

ON-OFF/ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI+

SDCM <3

Micro Prismatic Diffuser/ PMMA

L70 @50,000h

Aluminium

Types

Pendant/Recessed

Single Line Diagram


Profile Code

SY-56




Profile Code

SDL-1046



Profile Code


SDL-1036



PG SLIM CURVE

Lifx Trimless Curve linear fixture has :

- LED curved linear
- Extruded Aluminium Luminaire Housing
- Premium Finish Powder coating
- High efficiency Micro Prismatic/ PMMA Diffuser
- Uniform illumination
- Dot-free lighting and smart arc linear
- Infinite architectural designs and circular patterns possible
- Energy efficient LED with high colour rendering
- LED PCB mounted
- For pendant or recessed mounted applications
- Pendant using suspension cable with M6 bolt and fastener
- Bottom opening for easy maintenance



CRI ≥ 90



TUNABLE
WHITE

PG SLIM CURVE



PG SLIM CURVE

System Power	Dimensions
7W	L= 300mm
14W	L= 600mm
21W	L= 900mm
28W	L= 1200mm
56W	L= 2400mm

Order Options

Distribution

Direct

CCT (Color Temperature)

3000K
4000K
5700K
Tunable 2700K-6500K



CRI

>90

Beam Angle

Diffused

Control

ON-OFF
ON-OFF (FLICKER FREE)
DALI-2 DT6
DALI-2 DT8
DALI +



Mounting Type

Pendent
Recessed

Material Color

RAL As Per Request

Photometric Details
Photometric Details

