


PHONEIX 60 TRACK LIGHT

Direct | Track Mounted



Phoneix Track Light Luminaire housing of die cast-aluminum and with premium powder coating finish.

Powered by high-quality COB (Chip on Board) technology with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90 . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long-term reliability. Optics of high efficiency lens with 4beam angle options of 12°/24°/38°/55° + Efficient lens & reflector for uniform light distribution. This fixture has 355° rotatable along with vertical axis.


With a size of 60mm dia, and 180mm height, this fixture is crafted for direct light distribution making it ideal for professional applications.

Customisations in RAL finish, Wattages available as per request to enhance installation and functionality

Single Line Diagram

Track Mounted

PHONEIX 60



PHONEIX TRACK LIGHT



Quick Info

Mounting Type

Track Mounted

Material Colour

Powder Coated (Black & White)

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

12°

24°

38°

55°

Optics

Lens

Reflector

Efficacy

3000k- 91.6

4000k- 103.8

5700k- 116.2

Tunable White 2700K-6500K- 103.8

Electrical

Wattage - 10W

Input Voltage- 220-240 VAC

Physical

Dia- 60mm

Height- 180mm