PHOENIX 70 WALL WASHER

Direct | Track Mounted



PHOENIX 70 WALL WASHER Luminaire housing of die cast-aluminum and Die cast heat sink with premium powder coating finish.

Powered by high-quality COB (Chip on Board) technology with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90. The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long-term reliability. Optics of high efficiency lens with 2 beam angle options of Wall Washer inclination on the horizontal plane. Efficient lens & reflector for uniform light distribution. This fixture has 355° rotatble along with vertical axis. Suitable for non-magnetic surface and suspended tracks. With a size of 70mm dia, and 150mm height, this fixture is crafted for direct light distribution making it ideal for professional applications.


Customisations in RAL finish,

Wattages available as per request to enhance installation and functionality. Angle can be direct as per request.

Single Line Diagram

Track Mounted

PHONEIX 70 WALLWASHER



PHOENIX 70 WALL WASHER



Quick Info

Mounting Type

Track Mounted

Material Colour

Powder Coated (Black or White)

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤3 SDCM

Beam Angle

Wall Washer

Optics

Lens

Reflector

Efficacy

80lm/W

Electrical

Wattage - 20W

Input Voltage- 220-240 VAC

Physical

Dia- 70m

Height- 150mm

divinity lights

Address: Plot No-A-89, RIICO Industrial Area, Karoli, Bhiwadi, Rajasthan 301019.

www.divinitylights.com