

PHOENIX TRACK LIGHT

divinity lights



Quick Info

CRI ≥ 90

3000K/ 4000K/ 5700K

Tunable White (2700K-6500K)

ON-OFF/ON-OFF (FLICKER FREE)

DALI-2 DT6/ DALI-2 DT8 / DALI +

SDCM<3

Lens & Reflector

L70 @50,000h

Aluminium Die-cast


Types

Track Mounted


Single Line Diagram

Track Mounted


PHONEIX 60




PHONEIX 70



PHONEIX 80



PHONEIX 90




Colours



Light Distribution


Direct



CRI ≥ 90



TUNABLE WHITE



PHOENIX TRACK LIGHT

Phoenix Track Light has :

- Die cast- aluminium Luminaire housing
- Die cast heat sink
- Premium powder coated finish
- COB (Chip on Board) technology
- LED with effective colour rendering
- Efficient lens & reflector for uniform light distribution
- Vivid & accurate lighting effect
- 355 degrees rotatable along vertical axis
- Suitable for non-magnetic Surface and Suspended Tracks
- Suitable for retail, hospitality & residential application

PHONEIX TRACK LIGHT



PHONEIX 60

Product Order Code	System Power	Dimension
5001-  1	10W	Dia = 60mm, H = 180mm

PHONEIX 70

Product Order Code	System Power	Dimension
5001-  2	20W	Dia = 70mm, H = 180mm

PHONEIX 80

Product Order Code	System Power	Dimension
5001-  3	30W	Dia = 80mm, H = 180mm

PHONEIX 90

Product Order Code	System Power	Dimension
5001-  4	40W	Dia = 90mm, H = 180mm

Order Options

Distribution

Direct

CCT (Colour Temperature)	
3000K	1
4000K	2
5700K	3
Tunable White 2700K-6500K	4



CRI	
>90	1

Beam Angle	
12°	1
24°	2
38°	3
55°	4


Control		
ON-OFF		1
ON-OFF (FLICKER FREE)		2
DALI-2 DT6		3
DALI-2 DT8		4
DALI +		5

Material Colour	
Black	 1
White	 2
Grey	 3

Mounting Type

Track Mounted

Accessories

Product Order Code	Accessories Name	Accessories Image
5001-01 	COB	

Order Options

CCT (Colour Temperature)		
3000K		1
4000K		2
5700K		3
Tunable White 2700K-6500K		4
CRI		
>90		1