

## RAYS-20 EN

ENCAPSULATED LINEAR LIGHT

Direct | Surface

### RAYS-20 EN

ENCAPSULATED LINEAR LIGHT

## RAYS-20 ENCAPSULATED



## Quick Info

### Mounting Type

Surface

### Material Colour

Customize RAL available

### Protection mode

IP65

### Driver Details

Non-Dimmable/ Dali-Dimmable/ DMX512 Controller

Power Factor (PF) -0.95

THD- <10%

UGR - <19

### LED

CCT- 2400K/ 2700K/ 3000K/ 4000K/ RGB/ RGBW

CCT- Lens with Mono color DMX 100mm pixel pitch

CCT- RGBW DMX 250 mm pixel pitch

CRI- ≥ 80

Life Span - L70@50000h

MacAdam - <3 SDCM

### Beam Angle

15°/ 35°/ 55°/ 10X55°

### Optics

Lens with Potted

### Efficacy

80lm/W

### Electrical

Wattage - 20W

Input Voltage- 24V DC

### Physical Dimensions

Length- 1000mm

Width- 22.7mm

Height- 23.5mm

**RAYS-20 EN** Encapsulated Linear Light is a versatile and high-performance linear lighting solution designed for architectural, decorative and façade lighting applications. Its compact linear profile combines a robust encapsulated construction with precision optics, making it suitable for creating continuous and controlled illumination on walls, ceilings and architectural surfaces. The fixture supports both monochromatic and dynamic lighting configurations, including RGB and RGBW, allowing designers to create customized lighting effects for different architectural environments.

With its encapsulated construction, multiple beam-angle options and DMX-compatible configurations, RAYS-20 EN is ideal for wall grazing, architectural façades, feature walls, ceilings, commercial spaces, hotels, resorts, landscape structures and decorative architectural installations. Its compact profile allows discreet integration into architectural details while providing precise and continuous illumination.

Divinity Lights manufactures customized lighting solutions according to clients' specific requirements, making RAYS-20 EN suitable for tailored architectural and dynamic lighting projects.

### Single Line Diagram

Surface

