


RING CATENARY LIGHTS

Direct | Catenary

RING CATENARY LIGHTS




RING CATENARY LIGHT RING CATENARY LIGHT is a contemporary suspended outdoor luminaire designed to provide functional and decorative illumination across large open architectural and landscape spaces. Featuring a clean circular profile and a slim aluminium die-cast housing, the fixture delivers an elegant visual presence while providing uniform illumination with minimal multiple shadows. Its catenary-mounted design makes it ideal for installation over plazas, pathways, walkways, public spaces, courtyards, outdoor dining areas and architectural landscapes. The luminaire is available with multiple finish options and customized RAL colours to complement different environments.

With a 1200 mm diameter and 21 mm overall height, RING CATENARY LIGHT combines a slim construction with a distinctive circular form. Its aluminium die-cast housing and finned heat-sink design help dissipate heat and support reliable performance, while the suspended configuration provides efficient area lighting without obstructing pedestrian movement. Divinity Lights provides customized lighting solutions according to clients' specific project requirements.

Single Line Diagram

Catenary Mounted



RING CATENARY LIGHTS



Quick Info

Mounting Type

Catenary

Material Colour

Customize RAL available

Protection mode

IP66

Driver Details

Non-Dimmable/ Dali-Dimmable

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 2700K/ 3000K/ 4000K

CRI- ≥ 80

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

120°

Optics

Potted Diffuser

Efficacy

80lm/W

Electrical

Wattage - 70W

Input Voltage- 24V DC

Physical Dimensions

Dia- 1200mm

Height- 21mm