RIVEN 370
WALL WASHER
Direct | Surface

RIVEN 370 WALL WASHER by Divinity Lights features a sleek design with a robust extruded aluminium housing and premium powder-coated finish, delivering durability and a refined appearance for architectural lighting applications.

Powered by high-quality LEDs with a binning tolerance of < 3 SDCM and CRI > 80, the luminaire maintains at least 70% of its luminous flux after 50,000 operating hours, ensuring reliable long-term performance. Its precision-engineered lens optics provide uniform illumination, while the IP66 protection rating ensures suitability for demanding outdoor environments.

With a standard size of 370.2mm length, 124.7mm width, and 189.9mm height, this 50W wall washer delivers efficient and controlled lighting for architectural façades, building exteriors, landscape features, and commercial spaces.

Divinity Lights offers customization in RAL finishes, wattages, and lengths according to clients' specific requirements, providing tailored lighting solutions that enhance both aesthetics and functionality.

Single Line Diagram

Surface Mounted



RIVEN 370 WALL WASHER

INPUT VOLTAGE 220V AC/ 24V DC | IP66 | CRI >80

Quick Info

Mounting Type
Surface

Material Colour
Customize RAL available

Protection mode
IP66

Driver Details
Non-Dimmable/ Dali-Dimmable/ DMX 512
Power Factor (PF) -0.95
THD- <10%
UGR - <19

LED
CCT- 2700K/ 3000K/ 4000K/ RGBW, RGB
CRI- ≥ 80
Life Span - L70@50000h
MacAdam - ≤3 SDCM

Beam Angle
30°

Optics
Lens

Efficacy
40lm/W

Electrical
Wattage - 50W
Input Voltage- 220V AC/ 24V DC

Physical Dimensions
Length- 370.2mm
Width - 124.7mm
Height- 189.9mm

divinity lights

Address: Plot No-A-89, RIICO Industrial Area, Karoli, Bhiwadi, Rajasthan 301019.

www.divinitylights.com