divinity lights



CRI ≥ 80 /90

2700K, 3000K, 4000K

Up to 15 lm/W

Non-Dimmable/Dali-Dimmable

SDCM<3

Clear Glass


L70 @50,000h

Aluminium Die-Cast

Types

Recessed


Single Line Diagram











RAY

RAY Step light has:

- Luminaire housing of Die-Cast Aluminium
- IP65, High Ingress Protection against dust & moisture
- Extremely sustainable and requires little maintenance
- Lens optics for even light distribution
- Energy-efficient LED with high colour rendering
- Precise narrow beam of 15°
- Perfect for lighting pathways and driveways, steps and gardens
- Sleek & sophisticated recessed mounted LED light designed to elevate your outdoor lighting experience

Light Distribution





CRI ≥ 80/90

divinity lights

RAY









Product Order Code	System Power	Dimensions
1788	3W	L=210mm, W=49mm H=68mm

Order Options

CCT (Colour Temperature)		
2799K		
3000K		
4000K		
CRI		
>80		
>90		
D 4 1		
Beam Angle		
15°		
Control		
Non-Dimmable	XXII Committee	
Dali-Dimmable		
Marina Trans		
Mounting Type		
Recessed		
Material Colour		
Black	•	
Grey		