

SHINE

divinity lights



CRI ≥ 90

3000K/ 4000K/ 5700K

Tunable white (2700K-6500K)

ON-OFF/ ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI+

SDCM <3

PMMA Diffuser



L70 @50,000h

Aluminium

Types

Surface

Single Line Diagram



SHINE

Shine Led Strip with profile :


- Luminaire housing made of aluminium
- Creates a wash of ambient and vertical illumination between the wall & ceiling plane
- For use in offices, hallways, conference rooms, medical facilities, etc.
- Uniform illumination
- Energy efficient LED
- Effective colour rendering
- Unique straight-line style (LED Profile)
- LED Profiles made of aluminium to add a premium look

Colours



Light Distribution

Direct



CRI ≥ 90






TUNABLE
WHITE


SHINE




SHINE

Product Order Code	System Power	Dimension
7009-  1	5W	L=1000mm, W=15mm, H=6mm
7009-  2	10W	L=1000mm, W=15mm, H=6mm
7009-  3	15W	L=1000mm, W=15mm, H=6mm





Order Options

CCT (Colour Temperature)	
WW NW	1
CCT	2
RGB	3

CRI	
>90	1

Beam Angle

24°	
-----	--

Control	
DALI-2 DT6	 1
DALI-2 DT8	 2
DALI+	 3

VOLTAGE

24V DC	
--------	--

Mounting

Surface	
---------	--