

divinity lights

SORIO-U



## Quick Info

CRI  $\geq 90$

3000K/ 4000K/ 5700K

Tunable White 2700-6500K

ON-OFF/ ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI+

SDCM $<3$

Lens

L70 @50,000h

Aluminium


## Types

Pendant


## Single Line Diagram

Pendant Mounted

Profile Code  
SDL-3005




Profile Code  
SDL-3006



## SORIO-U

Sorio-U fixture has

- Extruded Aluminium Luminaire Housing
- Premium Finish Powder coating
- High efficiency Lens
- Energy efficient LED with high colour rendering
- LED PCB mounted on insert design with heat sink
- Snap-fit system and no visible screw
- Unique curved design and patterns possible
- Pendant using suspension cable with M6 bolt and fastener
- Bottom opening for easy maintenance



CRI  $\geq 90$



TUNABLE WHITE

SORIO-U



SORIO-U (DIRECT)

System Power	Dimensions
5W	L = 300mm
10W	L = 600mm
15W	L = 900mm
20W	L = 1200mm
40W	L = 2400mm

Order Options

Distribution

Direct

CCT (Color Temperature)

3000K  
4000K  
5700K  
Tunable 2700K-6500K



CRI

>90

Beam Angle

24°  
38°  
55°

Control

ON-OFF  
ON-OFF (FLICKER FREE)  
DALI-2 DT6  
DALI-2 DT8  
DALI +



Mounting Type

Pendent

Material Color

RAL As Per Request