


SILIONA 32

divinitylights



Quick Info

CRI \geq 90/ 95

3000K/ 4000K/ 5700K/ 6500K

Tunable White (2700K-6500K)

System lumen > 100 lm/W

ON-OFF/ON-OFF (FLICKER FREE)

DALI-2 / DALI-2 DT8 / D4i / DALI +

POE (Power Over Ethernet)

SDCM<3

Silicon Diffuser

L70 @50,000h


Aluminium

Types


Pendant

Single Line Diagram

Profile



Silicon Diffuser




Colours



Light Distribution

Direct



CRI \geq 90/ 95



TUNABLE WHITE

SILIONA 32 LINEAR

Siliona 32 linear fixture has:

- Extruded Aluminium Luminaire Housing
- Premium Finish Powder coating
- High efficiency silicon diffuser
- 280 degree uniform light distribution
- Energy efficient LED with high colour rendering
- LED PCB mounted on insert design with heat sink
- Snap-fit system and no visible screw
- Pendant using suspension cable with M6 bolt and fastener
- Bottom opening for easy maintenance

SILIONA 32



Product Order Code	System Power	Dimension
1035-1	4W	L=300mm, Ø 32mm
1035-2	9W	L=600mm, Ø 32mm
1035-3	13W	L=900mm, Ø 32mm
1035-4	17W	L=1200mm, Ø 32mm
1035-5	34W	L=2400mm, Ø 32mm

Order Options

Distribution

Direct

Lumen Type

- Low 1
- High 2

CCT (Colour Temperature)

- 3000K 1
- 4000K 2
- 5700K 3
- 6500K 4
- Tunable White 2700K-6500K 5

CRI

- >90 1
- >95 2

Beam Angle

280°

Control

- ON-OFF 1
- ON-OFF (FLICKER FREE) 2
- DALI-2 3
- DALI-2 DT8 4
- DALI + 5
- D4i 6
- POE (Power Over Ethernet) 7





Mounting Type

- Pendant 1

Material Colour


- Black
- White
- Grey

Accessories

Product Order Code	Accessories Name	Accessories Image
1035-01 <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	LED PCB	
1035-02	Suspension Wire	
1035-03	Silicon Diffuser	
1035-04	End Cap	

Order Options

Lumen Type	<input checked="" type="checkbox"/>
Low	1
High	2

CCT (Colour Temperature)	<input checked="" type="radio"/>
3000K	1
4000K	2
5700K	3
6500K	4
Tunable White 2700K-6500K 	5

CRI	<input checked="" type="radio"/>
>90	1
>95	2