

## SIRI

Siri Wall light has :

- Luminaire housing of Die-Cast Aluminium
- IP65, High Ingress Protection against dust & moisture
- Wall mounted LED light
- Easy to install & maintain
- Lens optics for even light distribution
- Energy-efficient LED with high colour rendering
- High efficacy & lower consumption
- Suitable for hotels, department stores, yards, doorways, porches, gardens, pathways
- Fitting projects the light in an upward & downward direction and ensures even light distribution in both directions

### Quick Info

CRI ≥ 80 /90

2700K, 3000K, 4000K

Up to 85 lm/W

Non-Dimmable/ Dali-Dimmable

SDCM<3

Lens

L70 @50,000h


Aluminium Die-Cast

### Types



Surface

### Single Line Diagram

Direct



Direct-Indirect



CRI ≥ 80/90

## SIRI



### SIRI (DIRECT)

Product Order Code	System Power	Dimensions
1752	6W	L=120mm W=110mm H=100mm

### SIRI (DIRECT-INDIRECT)

Product Order Code	System Power	Dimensions
1753	2X6W	L=120mm W=110mm H=120mm

## Order Options

### CCT (Colour Temperature)

2700K  
3000K  
4000K

### CRI

>80  
>90

### Beam Angle

80°  
2X80°

### Control

Non-Dimmable



Dali-Dimmable



### Mounting Type

Surface

### Material Colour

Black



Grey

