

Quick Info

CRI ≥ 80 /90

2700K, 3000K, 4000K

Up to 80 lm/W

Non-Dimmable/ Dali-Dimmable/

DMX Controller

SDCM<3

Transparent Glass




L70 @50,000h

Aluminium Die-Cast

Types

Surface


Single Line Diagram



STERLING 53

Sterling 53 Pixel light has :

- Luminaire housing of Aluminium
- IP66, High Ingress Protection against dust & moisture
- Class 3 electrical safety ensures effective stability of the lamp in an outdoor environment for all weather conditions
- Flexible mounting performance for a variety of irregular structures
- Different colour options available including Monocolour, RGB & RGBW
- Suitable for curtain walls, large building displays, decorations, 3D shapes, etc.
- Colour resolution of 16 bits
- Anti-shock ability
- Fire protection rating UL94-V0



CRI ≥ 80/90

STERLING 53



Product Order Code	System Power	Dimensions
1822	2W/LED	L=67mm, W=53.8mm, H=17.4mm

Order Options

CCT (Colour Temperature)

2700K

3000K

4000K

RGB

CRI

>80

>90

Beam Angle

60°

120°

Control

Non-Dimmable



Dali-Dimmable



DMX Controller



Mounting Type

Surface

Material Colour

Black



White

