

TRIBER WALL WASHER

Direct | Surface

TRIBER WALL WASHER



TRIBER WALL WASHER by Divinity Lights features a compact, contemporary design with a precision-engineered housing and premium powder-coated finish, delivering durability and a refined appearance for architectural lighting applications.


Powered by high-quality LEDs with a binning tolerance of ≤ 3 SDCM and CRI ≥ 80 , the luminaire maintains at least 70% of its luminous flux after 50,000 operating hours, ensuring reliable long-term performance. Equipped with high-efficiency optics and a lens system, it delivers precise $45^\circ/53^\circ \times 110^\circ$ beam angle options for uniform wall illumination and reduced glare.

With a standard size of 116.9mm length, 102.9mm width, and 67.9mm height, this 10W fixture is designed for surface mounting and professional outdoor applications. Its IP66 protection rating ensures enhanced resistance to dust and water.

Divinity Lights offers customization in RAL finishes, wattages, and other specifications according to clients' specific requirements, making it suitable for façades, commercial buildings, hotels, landscapes, and architectural structures.

Single Line Diagram

Surface Mounted



TRIBER WALL WASHER



Quick Info

Mounting Type

Surface

Material Colour

Customize RAL available

Protection mode

IP66

Driver Details

Non-Dimmable/ Dali-Dimmable/ DMX512

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 2700K, 3000K, 4000K, RGBW

CRI- ≥ 80

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

$45^\circ/53^\circ \times 110^\circ$

Optics

Lens

Efficacy

70lm/W

Electrical

Wattage - 10W

Input Voltage- 220V AC/ 24V DC

Physical Dimensions

Length- 116.9mm

Width - 102.9mm

Height- 67.9mm