TRIBER
WALL WASHER
Direct | Surface

TRIBER WALL WASHER by Divinity Lights features a compact, contemporary design with a precision-engineered housing and premium powder-coated finish, delivering durability and a refined appearance for architectural lighting applications.

Powered by high-quality LEDs with a binning tolerance of ≤ 3 SDCM and CRI ≥ 80, the luminaire maintains at least 70% of its luminous flux after 50,000 operating hours, ensuring reliable long-term performance. Equipped with high-efficiency optics and a lens system, it delivers precise 45°/53°*110° beam angle options for uniform wall illumination and reduced glare.

With a standard size of 116.9mm length, 102.9mm width, and 67.9mm height, this 6W fixture is designed for surface mounting and professional outdoor applications. Its IP66 protection rating ensures enhanced resistance to dust and water.

Divinity Lights offers customization in RAL finishes, wattages, and other specifications according to clients' specific requirements, making it suitable for façades, commercial buildings, hotels, landscapes, and architectural structures.

Single Line Diagram

Surface Mounted



TRIBER WALL WASHER

INPUT VOLTAGE 220V AC/ 24V DC | IP66 | CRI >80

Quick Info

Mounting Type
Surface

Material Colour
Customize RAL avilable

Protection mode
IP66

Driver Details
Non-Dimmable/ Dali-Dimmable/ DMX512
Power Factor (PF) -0.95
THD- <10%
UGR - <19

LED
CCT- 2700K, 3000K, 4000K
CRI- ≥ 80
Life Span - L70@50000h
MacAdam - ≤3 SDCM

Beam Angle
45°/ 53*110°

Optics
Lens

Efficacy
70lm/W

Electrical
Wattage - 6W
Input Voltage- 220V AC/ 24V DC

Physical Dimensions
Length- 116.9mm
Width - 102.9mm
Height- 67.9mm

divinity lights

Address: Plot No-A-89, RIICO Industrial Area, Karoli, Bhiwadi, Rajasthan 301019.

www.divinitylights.com