

UNIK OUTER LIT RING

Direct | Pendant



UNIK OUTER LIT RING is sleek and slim circular led Ring luminaire in aluminium housing and with premium powder coating finish.



Powered by high quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90 . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency PMMA diffuser provides uniform illumination.

FOR 600mm Disc

Available in 600mm diameter, height of 20mm and profile of thickness 8mm, this fixture is crafted for side lit light distribution making it ideal for professional and decorative applications.

Customisations in RAL finish, Wattages and Dimensions available as per request to enhance installation and functionality.

Single Line Diagram



UNIK OUTER LIT RING



Quick Info

Mounting Type

Pendant

Material Colour

Customize RAL available

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤ 3 SDCM

Beam Angle

110°

Optics

Opal Diffuser

Efficacy

3000K- 85.1

4000K- 98.7

5700K- 113.4

Tunable White 2700K-6500K- 98.7

Electrical

Wattage -30W

Input Voltage- 220-240 VAC

Physical Dimensions

Dia- \varnothing 600mm

Height- 20mm

Profile Thickness- 8mm