VANICE BOLLARD



divinitylights

divinity lights

100





VANICE BOLLARD

Vanice Bollard fixture has:

- Luminaire housing of Aluminium
- IP66, High Ingress Protection against dust & moisture
- Flicker free operation for eye protection
- Energy-efficient LED with high colour rendering
- The built quality ensures long and maintenance free service life
- Optimum for every outdoor space including society parks, streets, educational institutes, and pathways
- Garden & pathway luminaires create pleasant light distribution with a high degree of visual comfort
- LED bollard, designed to provide radially symmetric light emission of 360°
- Sustainable LED technology offers durability and optimal light output with low power consumption

Quick Info

CRI ≥ 90 2700K, 3000K, 4000K

Non-Dimmable/ Dali-Dimmable SDCM<3 Clear Diffuser L70 @50,000h Aluminium Die-Cast

Types

Surface

Single Line Diagram





CRI ≥ 90

divinity lights

VANICE BOLLARD

UNPUT VOLTACE 24V DC IP66	(RI ≥ 90	
Product Order Code	System Power	Dimensions
1873	10W	LXW=100mmX100mm H=1000mm

Order Options

CCT (Colour Temperature) 2700K 3000K 4000K CRI >90 Beam Angle N.A Control Non-Dimmable Dali-Dimmable Mounting Type

Surface

Material Colour

Grey