

VIRAJ 45

Direct | Pendant



Linear shaped light fitting in die-cast aluminium; Extremely slim design; Black powder coated on surface; Suspended luminaire with adjustable pendant rod mounting (chrome) 1000mm, feed in rod; Electronic operating unit installed in canopy; Blind cover to cover the cut-outs, accessories listed separately; Light colour 3000K; Binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; Minimum 90% of luminous flux after 50000 operating hours; Energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; Direct / indirect radiation characteristic for additional accentuation of the ceiling; Degree of protection IP20; PC1 220-240V; Photobiological safety according to IEC 62471 risk group RG 0 - no risk; Internal wiring in the light halogen free; Including DALI-2 converter; Light source can be replaced by an authorised professional; The control gear may be replaced by an authorized professional.

VIRAJ 45



Quick Info

Mounting Type

Pendant

Material Colour

Customize RAL avilable

Protection mode

IP40

LED

CCT- 3000K

CRI- ≥ 90

Life Span-L70 @ 50000h

MacAdam- ≤ 3 SDCM

Efficacy-102.7lm/w

Control

ON-OFF

Optics

Opal Diffuser

Prismatic Diffuser

Lens

Electrical

Wattage-25W

Input- 220-240 VAC


Physical

Lenght- 1200mm

Height- 70 mm

Width- 46 mm

LUMINOUS INTENSITY DISTRIBUTION



PRODUCT DRAWING

