

VIRAJ 45 LENS

Direct | Pendant



VIRAJ 45



Quick Info

Mounting Type

Pendant

Material Colour

Customize RAL available

Protection mode

IP40

McAdam- 3

Power Factor (PF) - 0.95

THD - <10%

UGR - <21

LED

CCT- 3000K/4000K/5700K/TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span-L70 @ 50000h

MacAdam- ≤ 3 SDCM

Efficacy-102.3 lm/w

Control

DALI DIMMABLE/ NON DIMMABLE/ DALI-2 DT8

Beam Angle

38°

Optics

Lens

Electrical

Std Wattage - 28W/4ft

Opt Wattages Available -15W/4ft,20W/4ft,25W/4ft

Input- 220-240 VAC

Physical

Length- 1200 mm

Height- 70 mm

Width- 46 mm

Viraj 45 Lens Linear luminaire in a sleek design with a slim Extruded aluminium housing and with premium powder coating finish.

Powered by high quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90 . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. Deep recessed lens and reflector for better uniformity.

With a standard size of 1200mm length, 70mm height, and 46mm width, this fixture is crafted for direct light distribution making it ideal for professional applications.

Customisations in RAL finish, Wattages and Length available as per request to enhance installation and functionality.

Single Line Diagram

Pendant

