

# divinity lights

#### **Quick Info**

CRI ≥ 90


3000K/ 4000K/ 5700K
Tunable White 2700K-6500K
ON-OFF/ON-OFF (FLICKER FREE)
DALI-2 DT6 / DALI-2 DT8/ DALI +
SDCM<3

Micro Prismatic Diffuser L70 @ 50,000h Aluminium

#### **Types**

Pendant/Surface

### **Single Line Diagram**









## **VIRAJ 50 SLIDER**

Viraj 50 slider sleek and slim linear fixture has:

- Extruded Aluminium Luminaire Housing
- Premium Finish Powder coating
- High-performance PMMA & Micro Prismatic Diffuser
- High-performance Prismatic double-sliding diffuser
- LED PCB mounted on insert design with heat sink
- Energy efficient LED with high colour rendering
- Snap- fit system
- No visible screw
- Pendant using suspension cable with M6 bolt and fastener
- Bottom opening for easy maintenance

#### **Colours**








### **Light Distribution**

Direct Direct-Indirect









CRI ≥ 90

TUNABLE WHITE

# divinity lights

### **VIRAJ 50 SLIDER**











## VIRAJ 50 SLIDER ( DIRECT )

Product Order Code	System Power	Dimensions	
1006-1	7W	L = 300mm, W = 51mm, H = 75mm	
1006-1፬◉◐	14W	L = 600mm, W = 51mm, H = 75mm	
1006-1॑॓○●●  □ 3	21W	L = 900mm, W = 51mm, H = 75mm	
1006-1॑00 • □	28W	L = 1200mm, W = 51mm, H = 75mm	
1006-1◘●●■ ── 5	56W	L = 2400mm, W = 51mm, H = 75mm	

## VIRAJ 50 SLIDER ( DIRECT-INDIRECT )

Product Order Code	System Power	Dimensions
1006-▼◎●●■101	9W	L = 300mm, W = 51mm, H = 75mm
1006-▼□●●■1○2	18W	L = 600mm, W = 51mm, H = 75mm
1006-▼□●●■13	27W	L = 900mm, W = 51mm, H = 75mm
1006-▼□●●■1○4	35W	L = 1200mm, W = 51mm, H = 75mm
1006-▼☑●◐■1○5	70W	L = 2400mm, W = 51mm, H = 75mm

## **Order Options**

Direct       1         Direct-Indirect       2         Up-50% / Down-50%       2         Up-30% / Down-30%       4         Up-20% / Down-80%       5         Up-80% / Down-20%       6         CCT (Colour Temperature)         3000K       1         4000K       2         5700K       3         Tunable White 2700K-6500K       4         CRI         >90       1         Beam Angle         110°       □         Control         ON-OFF       □         ON-OFF (FLICKER FREE)       □         DALI-2 DT-6       □         DALI-2 DT-6       □         DALI +       □         Mounting Type       □         Pendant       1         Surface       2         Material Colour       □         Black       1         White       2         Grey       3	Distribution		•
Up-50% / Down-50% 2 Up-30% / Down-70% 3 Up-70% / Down-30% 4 Up-20% / Down-80% 5 Up-80% / Down-20% 6  CCT (Colour Temperature) 3000K 1 4000K 2 5700K 3 Tunable White 2700K-6500K 4  CRI 90 1  Beam Angle 110°  Control ON-OFF U 1 ON-OFF (FLICKER FREE) 2 DALI-2 DT-6 3 DALI-2 DT-6 3 DALI-2 DT-6 3 DALI-2 DT-6 5 DALI-2 DT-6 5 Mounting Type Pendant 1 Surface 2  Material Colour  Black 1 White 2	Direct		1
Up-30% / Down-70%	Direct-Indirect		
Up-70% / Down-30%	Up-50% / Down-50%		2
Up-20% / Down-80%  Up-80% / Down-20%  CCT (Colour Temperature)  3000K 4000K 22 5700K 3 Tunable White 2700K-6500K  CRI >90 1  Beam Angle 110°  Control ON-OFF ON-OFF (FLICKER FREE) DALI-2 DT-6 DALI-2 DT-8 DALI-2 DT8 DALI +  Mounting Type  Pendant 1 Surface 2  Material Colour  Black White 2 2  5  Mounting Type  Part Angle 1 3 5  Mounting Type  Pendant 1 5  Mounting Type  Pendant 1 5  Material Colour  Black 1 White 2	Up-30% / Down-70%		3
Up-80% / Down-20%  CCT (Colour Temperature)  3000K	Up-70% / Down-30%		4
CCT (Colour Temperature)  3000K 4000K 5700K 3 Tunable White 2700K-6500K  CRI >90 1  Beam Angle 110°  Control ON-OFF (FLICKER FREE) DALI-2 DT-6 DALI-2 DT-8 DALI +  Mounting Type Pendant Surface 2  Material Colour  Black White 2  2  Material Colour  Black White 2  3  1  1  1  1  1  1  1  1  1  1  1  1	Up-20% / Down-80%		5
3000K 4000K 20 5700K 30 Tunable White 2700K-6500K  CRI >90 1  Beam Angle 1100  Control ON-OFF ON-OFF (FLICKER FREE) DALI-2 DT-6 DALI-2 DT8 DALI+ DALI+ DALI+ DALI+ DALI+ DALI+ DALI-2 DT8 D	Up-80% / Down-20%		6
4000K 5700K 3 Tunable White 2700K-6500K  CRI >90 1  Beam Angle 110°  Control ON-OFF ON-OFF (FLICKER FREE) DALI-2 DT-6 DALI-2 DT8 DALI+  Mounting Type Pendant Surface 2  Material Colour  Black White 2  2  5700K 3  4  CRI  A  A  A  A  A  B  A  A  B  A  B  A  B  A  B  A  B  A  B  A  B  A  B  A  B  A  B  A  B  A  B  A  B  A  B  A  B  A  B  B	•	ure)	
5700K Tunable White 2700K-6500K  CRI >90 1  Beam Angle 110°  Control ON-OFF ON-OFF (FLICKER FREE) DALI-2 DT-6 DALI-2 DT8 DALI +  Mounting Type Pendant 1 Surface 2  Material Colour  Black White 2  5  1  1  1  1  1  1  1  1  1  1  1  1			
Tunable White 2700K-6500K  CRI  >90  1  Beam Angle  110°  Control  ON-OFF  ON-OFF (FLICKER FREE)  DALI-2 DT-6  DALI-2 DT8  DALI +  Mounting Type  Pendant  Surface  1  Surface  Material Colour  Black  White  2			
CRI >90 1  Beam Angle 110°  Control  ON-OFF			
>90 1  Beam Angle  110°  Control  ON-OFF		2700K ———— 6500K	4
Beam Angle  110°  Control  ON-OFF  ON-OFF (FLICKER FREE)  DALI-2 DT-6  DALI-2 DT8  DALI+  Mounting Type  Pendant  Surface  2  Material Colour  Black  White  2  The state of t	CRI		
Control ON-OFF ON-OFF (FLICKER FREE) DALI-2 DT-6 DALI-2 DT8 DALI+  Mounting Type Pendant Surface 2  Material Colour  Black White 2	>90		1
Control  ON-OFF  ON-OFF (FLICKER FREE)  DALI-2 DT-6  DALI-2 DT8  DALI +  Mounting Type  Pendant  Surface  1  Surface  2  Material Colour  Black  White  2	Beam Angle		
ON-OFF (FLICKER FREE)  DALI-2 DT-6  DALI-2 DT8  DALI +  Mounting Type  Pendant  Surface  1  Surface  2  Material Colour  Black  White  2  1  1  1  1  1  1  1  1  1  1  1  1	1100		
ON-OFF (FLICKER FREE) 2  DALI-2 DT-6 3  DALI-2 DT8 DALI + 5  Mounting Type Pendant 1  Surface 2  Material Colour	Control		
DALI-2 DT-6  DALI-2 DT8  DALI + 5  Mounting Type  Pendant 1  Surface 2  Material Colour	ON-OFF	<u></u>	1
DALI-2 DT8  DALI +  Mounting Type  Pendant  Surface  2  Material Colour  Black  White  2	ON-OFF (FLICKER FREE)		2
DALI + 5  Mounting Type  Pendant 1  Surface 2  Material Colour   Black 1  White 2	DALI-2 DT-6	BALL	3
Mounting Type  Pendant 1  Surface 2  Material Colour   Black 1  White 2	DALI-2 DT8	DT8	4
Pendant 1 Surface 2  Material Colour   Black 1 White 2	DALI +	DALIĐ	5
Surface 2  Material Colour   Black 1  White 2	Mounting Type		
Material Colour   Black 1  White 2	Pendant		1
Black 1 White 2	Surface		2
White 2	Material Colour		$\bigcirc$
	Black		1
Grey 3	White		2
	Grey		3

# divinity lights

# Accessories

Product Order Code	Accessories Name	Accessories Image
1006-01⊠⊚€	LED PCB	
1006-02	Suspension Wire	
1006-03	PMMA Diffuser	
1006-04	Micro Prismatic Diffuser	
1006-05	Profile Connector	
1006-06	Profile Endcap	

# **Order Options**

CCT (Colour Temperature)		
3000K		1
4000K		2
5700K		3
Tunable White 2700K-6500K	2700K ———————————————————————————————————	4
CRI		•
>90		1
Material Colour		$\circ$
Black		1
White		2
Grey		3