

**VIRAJ 5690
DAISY**

divinity lights



VIRAJ 5690 DAISY LENS



**VIRAJ 5690 DAISY
LENS + DIFFUSER**

Lens

Micro Prismatic
Diffuser



divinity lights

Quick Info

CRI ≥ 90
 3000K/ 4000K/ 5700K
 Tunable White 2700K-6500K
 ON-OFF/ON-OFF (FLICKER FREE)
 DALI-2 DT6/ DALI-2 DT8 / DALI +
 SDCM<3
 Lens
 L70 @ 50,000h
 Aluminium


Types

Pendant/ Surface/ Recessed


Single Line Diagram

Pendant/Surface Mounted

Outer Profile Code
SY-101




Profile Insert Code
SY-105




Recessed Mounted

Outer Profile Code
SY-104




Profile Insert Code
SY-105



Light Distribution


Direct Direct-Indirect



CRI ≥ 90



TUNABLE
WHITE



VIRAJ 5690 DAISY

Viraj 5690 Daisy sleek and slim linear fixture has :

- Luminaire housing of extruded aluminium
- Snap-fit system
- Unique lens system
- 3 beam angles including 30°, 50° & 80° widespread
- LED PCB mounted on insert design with heat sink
- Bottom opening for easy maintenance
- Pendant with cable suspension
- M6 bolt for M6 fastener
- Snap-fit system and no visible screw
- Energy-efficient LED

VIRAJ 5690 DAISY



VIRAJ 5690 DAISY (DIRECT)

| System Power | Dimensions |
|--------------|------------|
| 7W | L = 300mm |
| 14W | L = 600mm |
| 21W | L = 900mm |
| 28W | L = 1200mm |
| 56W | L = 2400mm |

VIRAJ 5690 DAISY (DIRECT-INDIRECT)

| System Power | Dimensions |
|--------------|------------|
| 9W | L = 300mm |
| 18W | L = 600mm |
| 27W | L = 900mm |
| 35W | L = 1200mm |
| 70W | L = 2400mm |

Order Options

Distribution

- Direct
- Indirect
- Up-50% / Down-50%
- Up-30% / Down-70%
- Up-70% / Down-30%
- Up-20% / Down-80%
- Up-80% / Down-20%

CCT (Color Temperature)

- 3000K
- 4000K
- 5700K
- Tunable 2700K-6500K



CRI

>90

Beam Angle

78°

Control

- ON-OFF
- ON-OFF (FLICKER FREE)
- DALI-2 DT6
- DALI-2 DT8
- DALI +



Mounting Type

- Pendent
- Surface
- Recessed

Material Color

RAL As Per Request

Photometric Details

