

VIRAJ 70 LENS

Direct | Surface



VIRAJ 70 LENS Linear Luminaire in a sleek design with a slim Extruded aluminum housing and with premium powder coating finish.


Powered by high-quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90 . The luminaire maintains at least 70% of its luminous flux after 50,000 operating hours, guaranteeing long-term reliability. Deep recessed lens and reflector for better uniformity.

With a standard size of 1200 mm length, 110 mm height, and 77 mm width, this fixture is crafted for direct light distribution making it ideal for professional applications.

Customisations in RAL finish, Wattages and Length available as per request to enhance installation and functionality.

Single Line Diagram

Surface



VIRAJ 70 LENS



Quick Info

Mounting Type

Surface

Material Colour

Customize RAL available

Protection mode

IP40

MacAdam- 3

Power Factor (PF) - 0.95

THD - <10%

UGR - <21

LED

CCT- 3000K/4000K/5700K/TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span-L70 @ 50000h

MacAdam- ≤ 3 SDCM

Efficacy-102.7lm/w

Control

DALI DIMMABLE/ NON DIMMABLE/ DALI-2 DT8

Beam Angle

38°

Optics

Lens

Electrical

Std Wattage - 28W/4ft

Opt Wattages Available -15W/ 4ft, 20W/ 4ft

Input- 220-240 VAC

Physical

Length- 1200mm

Height- 110 mm

Width- 77 mm