


# VIRAJ 70

Direct | Recessed



## VIRAJ 70



### Quick Info

#### Mounting Type

Recessed

#### Material Colour

Customize RAL available

#### Protection mode

IP40

MacAdam- 3

Power Factor (PF) - 0.95

THD - <10%

UGR - <21

#### LED

CCT- 3000K/4000K/5700K/TUNABLE WHITE 2700K-6500K

CRI-  $\geq 90$

Life Span-L70 @ 50000h

MacAdam-  $\leq 3$  SDCM

Efficacy-102.7lm/w

#### Control

DALI DIMMABLE/ NON DIMMABLE/ DALI-2 DT8

#### Beam Angle

Diffused

#### Optics

Opal Diffuser

Prismatic Diffuser

#### Electrical

Std Wattage - 28W/4ft

Opt Wattages Available -15W/ 4ft, 20W/ 4ft

Input- 220-240 VAC

#### Physical

Length- 1200mm

Height- 80 mm

Width- 92 mm

Viraj 70 Linear luminaire in a sleek design with a slim Extruded aluminium housing and with premium powder coating finish.

Powered by high-quality LED's with a binning tolerance of  $\leq 3$  SDCM and CRI  $\geq 90$ . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long-term reliability. HPO diffuser (High-Performance Opal/ PMMA diffuser) provides uniform illumination.

With a standard size of 1200 mm length, 80mm height, and 92mm width, this fixture is crafted for direct light distribution making it ideal for professional applications.

Customisations in RAL finish, Wattages and Length available as per request to enhance installation and functionality.

### Single Line Diagram

