

VIRAJ DALINE





Quick Info

CRI ≥ 90

3000K/ 4000K/ 5700K

TUNABLE WHITE 2700-6500K

ON-OFF/ ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI+

SDCM <3

Reflector

L70 @50,000h

Aluminium


Types

Pendant/Surface/Recessed

Single Line Diagram


Pendant/Surface Mounted

Profile Code
SHF-1076




Recessed Mounted

Profile Code
SHF-1075



Light Distribution



CRI ≥ 90



TUNABLE
WHITE



VIRAJ DALINE

VIRAJ Daline light features has:

- Luminaire housing of extruded aluminium
- High-performance Reflector
- Snap-fit system No visible screw
- Better refractive index to reduce glare
- LED PCB mounted on insert design with heat sink
- Bottom opening for easy maintenance
- Pendant with cable suspension
- M6 bolt for M6 fastener
- Energy-efficient LED with high color rendering

VIRAJ DALINE



VIRAJ DALINE

System Power

Dimension

15W

L = 1200mm

Order Options

CCT (Colour Temperature)

3000K

4000K

5700K

Tunable White 2700K-6500K



CRI

>90

Beam Angle

65°

Control

ON-OFF



ON-OFF (FLICKER FREE)



DALI-2 DT6



DALI-2 DT8



DALI+



Mounting

Pendant

Surface

Material Colour

RAL As Per Request