

# VIRAJ DALINE

Direct | Surface



**VIRAJ DALINE** Linear luminaire in a sleek design with a slim Extruded aluminium housing and with premium powder coating finish.

Powered by high quality LED's with a binning tolerance of  $\leq 3$  SDCM and  $CRI \geq 90$ . The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. Deep recessed lens for better uniformity.

With a standard size of 1200mm length, 17.07mm height, and 16.03mm width, this fixture is crafted for direct light distribution making it ideal for professional applications.


Customisations in RAL finish, Wattages and Length available as per request to enhance installation and functionality.

## Single Line Diagram

### Surface Mounted

#### Profile Code

SHF-1076



## VIRAJ DALINE



## Quick Info

### Mounting Type

Surface

### Material Colour

Customize RAL available

### Protection mode

IP40

### Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

### LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI-  $\geq 90$

Life Span - L70@50000h

MacAdam -  $\leq 3$  SDCM

### Beam Angle

65°

### Optics

Lens & Reflector

### Efficacy

3000K- 109.1lm

4000K- 120.6lm

5700K- 138.8lm

Tunable white 2700k-6500k- 120.6lm

### Electrical

Wattage- 15W/4ft

Opt Wattage Available- 15W/4ft, 20W/4ft, 25W/4ft

Input Voltage - 220-240 VAC

### Physical

Length- 1200 mm

Height- 17.07 mm

Width- 16.03mm