


divinity lights

VIRAJ ISLA



divinity lights

Quick Info

CRI ≥ 90

3000K/ 4000K/ 5700K

Tunable White 2700-6500K

ON-OFF/ ON-OFF (FLICKER FREE)

DALI-2 DT6 / DALI-2 DT8/ DALI+

SDCM<3

Lens

L70 @50,000h

Aluminium

Types


Pendant/Surface

Single Line Diagram

Pendant/Surface Mounted

Profile Code

SDL- 3004



Lens



Dimensions: 276.0 mm x 36.0 mm

Height: 14.20 mm

~25 + 80° asymmetric oval beam



CRI ≥ 90



TUNABLE WHITE

VIRAJ ISLA

Viraj ISLA fixture has

- Extruded Aluminium Luminaire Housing
- Premium Finish Powder coating
- High efficiency Lens
- Energy efficient LED with high colour rendering
- LED PCB mounted on insert design with heat sink
- Snap-fit system and no visible screw
- Unique curved design and pattern possible
- Pendant using suspension cable with M6 bolt and fastener
- Bottom opening for easy maintenance
- Profile is Perfect for double height area

VIRAJ ISLA



VIRAJ ISLA

System Power	Dimensions
40W	L = 1200mm
54W	L = 2400mm

Order Options

Distribution

Direct

CCT (Color Temperature)

3000K
4000K
5700K
Tunable 2700K-6500K



CRI

>90

Beam Angle

~25 + 80° assymmetric oval beam

Control

ON-OFF
ON-OFF (FLICKER FREE)
DALI-2 DT6
DALI-2 DT8
DALI +



Mounting Type

Pendent

Material Color

RAL As Per Request