VIRAJ NEO

Direct | Pendant

VIRAJ NEO Linear Luminaire with Extruded aluminium housing and with premium powder coating finish.

Powered by high quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90. The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long term reliability. High efficiency Double Micro Prismatic diffuser provides glare control and uniform illumination.

With a standard size of 1200mm length, 52.88mm Width, 68mm Height , this fixture is crafted for direct light distribution, making it ideal for professional applications.

Customisations in RAL finish, Wattages and Length available as per request to enhance installation and functionality.

Single Line Diagram

Pendant Mounted

Profile Code
SDL-1044



VIRAJ NEO

INPUT 220-240 VAC | IP40 | CRI >90

Quick Info

Mounting Type
Pendant

Material Colour
Customize RAL avilable

Protection mode
IP40

Driver Details
ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +
Power Factor (PF) -0.95
THD- <10%
UGR - <19

LED
CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K
CRI- ≥ 90
Life Span - L70@50000h
MacAdam - ≤3 SDCM

Beam Angle
110°

Optics
Opal Diffuser
Micro Prismatic Diffuser

Efficacy
3000K- 96.4
4000K- 109.2
5700K- 124.6
Tunable White 2700K-6500K- 109.2

Electrical
Wattage - 20W/4ft
Opt Wattages Available -5W/4ft, 10W/4ft, 15W/4ft
Input Voltage- 220-240 VAC

Physical Dimensions
Length- 1200mm
Width- 52.88mm
Height- 68mm

divinity lights

Address: Plot No-A-89, RIICO Industrial Area, Karoli, Bhiwadi, Rajasthan 301019.

www.divinitylights.com