

# VIRAJ 45

Direct | Pendant



Linear shaped light fitting in die-cast aluminium; Extremely slim design; Black powder coated on surface; Suspended luminaire with adjustable pendant rod mounting (chrome) 1000mm, feed in rod; Electronic operating unit installed in canopy; Blind cover to cover the cut-outs, accessories listed separately; Light colour 5700K; Binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; Minimum 90% of luminous flux after 50000 operating hours; Energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; Direct / indirect radiation characteristic for additional accentuation of the ceiling; Degree of protection IP20; PC1 220-240V; Photobiological safety according to IEC 62471 risk group RG 0 - no risk; Internal wiring in the light halogen free; Including DALI-2 converter; Light source can be replaced by an authorised professional; The control gear may be replaced by an authorized professional.

## VIRAJ 45



## Quick Info

### Mounting Type

Pendant

### Material Colour

Customize RAL available

### Protection mode

IP40

### LED

CCT- 5700K

CRI-  $\geq 90$

Life Span-L70 @ 50000h

MacAdam-  $\leq 3$  SDCM

Efficacy-111.3lm/w

### Control

DALI

### Optics

Opal Diffuser

Prismatic Diffuser

Lens

### Electrical

Wattage-25W

Input- 220-240 VAC


### Physical

Length- 1200mm

Height- 70 mm

Width- 46 mm

### LUMINOUS INTENSITY DISTRIBUTION



### PRODUCT DRAWING

