VIRAJ H30

Direct | Pendant



VIRAJ H30 is Linear Luminaire in a sleek design with a slim Extruded aluminium housing and with premium powder coating finish.

Powered by high-quality LED's with a binning tolerance of ≤ 3 SDCM and CRI ≥ 90. The luminaire maintains atleast 70% of its luminous flux after 50,000 operating hours, guaranteeing long-term reliability. High efficiency PMMA diffuser provides uniform illumination.

With a standard size of 1200 mm length, 64.67 mm height and 33.24 mm width, this fixture is crafted for direct light distribution making it ideal for professional applications.

Customisations in RAL finish, Wattages and Length available as per request to enhance installation and functionality.

Single Line Diagram

Pendant Mounted

Profile Code

SY-44



VIRAJ H30



Quick Info

Mounting Type

Pendant

Material Colour

Customize RAL avilable

Protection mode

IP40

Driver Details

ON/OFF/, DALI-2 DT6 / DALI-2 DT8/ DALI +

Power Factor (PF) -0.95

THD- <10%

UGR - <19

LED

CCT- 3000K/ 4000K/ 5700K/ TUNABLE WHITE 2700K-6500K

CRI- ≥ 90

Life Span - L70@50000h

MacAdam - ≤3 SDCM

Beam Angle

Diffused

Optics

PMMA Diffuser

Efficacy

3000K- 96.2lm

4000K- 103.4lm

5700K- 116.0lm

TUNABLE WHITE 2700k-6500k - 103.4lm

Electrical

Wattage- 25W/4ft

Opt Wattages Available -15W/4ft, 20W/4ft

Input Voltage- 220-240 VAC

Physical

Length- 1200 mm

Height- 64.67 mm

Width- 33.24 mm

divinity lights

Address: Plot No-A-89, RIICO Industrial Area, Karoli, Bhiwadi, Rajasthan 301019.

www.divinitylights.com